

JC662 U.S. PTO  
05/20/99

A

PATENTS

JC525 U.S. PTO  
09/315403  
05/20/99

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: )  
)  
**PHILLIP C. HWANG** )  
**WILLIAM PATRICK APPS** )  
**NORMAN E. STROHFUS** )  
**ROBERT W. GRACE** )  
**DAVID J. GLANCY** )  
)  
Serial No. )  
)  
Filed: CONCURRENTLY )  
)  
For: IMPROVED SHIPPING TRAY )

TRANSMITTAL


Commissioner of Patents and Trademarks  
Washington, D.C. 20231

Sir:

Transmitted herewith is Declaration and Power of Attorney; Specification; Cover Sheet; checks in the amount of \$928.00 to cover the filing fee and three (3) sets of drawings for the above-referenced patent application. These documents are being transmitted pursuant to the provisions of 37 C.F.R. 1.10 via Express Mail.

Respectfully submitted,

MILLER & MARTIN

By:   
Douglas T. Johnson  
Reg. No. 31,841

1000 Volunteer Building  
832 Georgia Avenue  
Chattanooga, Tennessee 37402-2289  
(615) 756-6600


Our Docket No. 46000-0001

Express Mail mailing label number: EE267242503US

Date of Deposit: 5/20/99

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Name of person mailing paper: Douglas T. Johnson



05/20/99 JC662 U.S. PRO

IN THE U.S. PATENT AND TRADEMARK OFFICE

Docket No. 46000-0001

Transmitted herewith for filing is the patent application of

Inventor: Phillip C. Hwang, William P. Apps, Norman E. Strohfus, Robert W. Grace and David J. Glancy

For: Improved Shipping Tray

Enclosed are:

- [X] Declaration and Power of Attorney (2)
- [X] Specification
- [X] 5 (3 each) formal sheets of drawing
- [ ] Four assignments of the invention resulting in ownership by Coca-Cola Enterprises, Inc.
- [ ] A certified copy of a \_\_\_\_\_ application
- [ ] A verified statement to establish small entity status under 37 C.F.R. §1.9 and 37 C.F.R. §1.27.
- [ ] Information Disclosure Statement

The filing fee has been calculated as shown below:

| FOR:                                   | NO. FILED | NO. EXTRA | Small Entity |     | Other than Small Entity |     |
|--|-----------|-----------|--------------|-----|-------------------------|-----|
|  |           |           | RATE         | FEE | RATE                    | FEE |
| BASIC FEE                              |           |           |              | 380 |                         | 760 |
| TOTAL CLAIMS                           | 25-20=    | 5         | x 9=         |     | x 18=                   | 90  |
| INDEP. CLAIMS                          | 4-3=      | 1         | x 39=        |     | x 78=                   | 78  |
| [ ] MULTIPLE DEPENDENT CLAIM PRESENTED |           |           | +130         |     | +260                    |     |
| [ ] LATE-FILING SURCHARGE              |           |           |              |     |                         |     |
|  |           |           | TOTAL        |     | TOTAL                   | 928 |

- [ ] Please charge my Deposit Account No. \_\_\_\_\_ in the amount of \$ \_\_\_\_\_. A duplicate copy of this sheet is enclosed.
- [X] The Commissioner is hereby authorized to charge any additional filing fees required under 37 C.F.R. §1.16, or credit any overpayment to Account No. 13-3403. A duplicate copy of this sheet is enclosed.
- [X] A check in the amount of \$928.00 to cover the filing fee for the enclosed.
- [ ] A check in the amount of \$160.00 to cover the assignment fees is enclosed.

Express Mail mailing label number EE267242503US


Date of Deposit: 5/20/99  
I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

By: Douglas T. Johnson

(Typed and printed name of person mailing paper or fee)

(Signature of person mailing paper or fee)

MILLER & MARTIN  
1000 Volunteer Building  
832 Georgia Avenue  
Chattanooga, Tennessee 37402  
(423) 756-6600

By:   
Douglas T. Johnson  
Reg. No. 31,841

APPLICATION FOR LETTERS PATENT  
UNITED STATES OF AMERICA

INVENTORS: Phillip C. Hwang  
William Patrick Apps  
Norman E. Strohfus  
Robert W. Grace  
David J. Glancy

TITLE: IMPROVED SHIPPING TRAY

Douglas T. Johnson  
Miller & Martin  
Suite 1000 Volunteer Building  
832 Georgia Avenue  
Chattanooga, Tennessee 37402  
(423) 756-6600  
(423) 785-8480 (Fax)

# **IMPROVED SHIPPING TRAY**

## **BACKGROUND OF THE INVENTION**

### **Field of the Invention**

This application claims the benefit of provisional applications 60/086,135 filed May 20, 1998 and 60/094,439 filed July 28, 1998 under 35 U.S.C. 119(e).

The present invention relates to an apparatus to facilitate the distribution of beverages, and particularly beverages with a limited shelf life or rapid sales turnover subject to frequent restocking, such as soft drinks. More particularly, the present invention relates to an improved shipping tray, which when utilized in its preferred embodiment, provides a nestable, lightweight shipping pallet of a moldable material.

### **Description of Related Art**

One current method of beverage distribution essentially considers the beverage truck driver a salesman. The driver's truck is loaded with a selection of beverages, and the driver calls on accounts on a route. At each account, the driver determines what beverages are required or desired by the account, then the driver locates the beverages in his truck, unloads the beverages and delivers them to the account. This process would be relatively easy if only a single beverage were involved. For instance, if the driver only distributed a single brand of cola, his truck would be completely loaded with that one beverage, and it could be easily unloaded at each account, and accounts could be serviced until the truck was completely empty.

However, today beverage brands are proliferating. In addition, a single brand of beverage may come in a variety of package styles and sizes, such as cans, glass bottles, and a range of plastic containers. When a beverage truck is loaded, as many as 350 different stock keeping units (SKU's) or brand/container combinations may be loaded. In order to facilitate access to so many different

SKU's, the most common beverage route truck is a side load truck, such as disclosed in U.S. Patent No. 4,043,569 or variations thereof, with about 12 to 20 separate compartments. In this fashion, usually no more than about ten different SKU's would have to be placed in a single compartment, although in some instances over 30 SKU's may be present. After determining an account's needed beverages, the driver goes to each separate compartment required to access those beverages. In some cases it will be necessary for the driver to unload a portion of a compartment to access the needed SKU. Furthermore, when a single SKU is exhausted from the truck's supply, the driver may no longer be able to properly service the remaining accounts on the route, even though the truck continues to have an adequate supply of other beverages. This leads to trucks returning to the distribution center partially loaded, and places a valuable premium upon correctly guessing the needs of the accounts on each route. Even when side load trucks are loaded to exact route requirements from account order information, the process of having the driver select SKU's from side load truck compartments is time consuming and back breaking work.

Accordingly, as part of a new beverage delivery system to improve delivery service it is desirable to utilize an improved shipping tray. Utilizing the improved shipping tray, a truck may be loaded to specifically meet the orders of each account on a route and to minimize the time needed to select and unload the beverages ordered by each individual account. Individual trays may be loaded with packages, or individual, beverage containers of various sizes and quantities including, for example cases, 6-packs or 2-liter bottles. The packaged units may be stacked in bays in truck trailers or in special carts loaded on a truck and then driven to a delivery point. Packaged units may be loaded in columns onto shipping trays in the desired types and quantity to satisfy an order by a particular retail location. Once at the retail location, the driver can unload the stacked shipping trays with a compatible hand truck or other manual carrier. When unloaded at the retail location, the

shipping tray may be used as the base for floor displays of the beverage products. This prevents damage to the products from the cleaning and floor waxing operations in the retail location.

The shipping tray provides an accessible area, below the stacked units, to receive the lifting portion, or tongue, of a hand truck. Therefore, the hand truck can readily be positioned under the shipping tray with the stacked packaged units. The packaged units may then be simply rocked into position onto the hand truck, transported to the display location and unloaded in a similar fashion. This system avoids, or reduces, manual lifting and re-stacking by the driver. Since the shipping tray is designed to accommodate case sized layers of SKU's, the SKU's can be pre-arranged in a column-stack on the shipping tray.

It is therefore an object of the present invention to provide improved shipping trays to facilitate both the loading and unloading of trucks with beverages sorted by account order.

Another object of the invention is to provide a durable, lightweight shipping tray for handling and transporting packages or packaged units such as beverage containers.

A further object of the present invention is to provide a low profile, nestable shipping tray which occupies relatively little space both when in a loaded stacked relation and when in an empty nested relation.

A further object of the present invention is to provide a lightweight, reusable shipping tray that can be efficiently and economically manufactured.

An additional object of the present invention is to provide a lightweight shipping tray of unitary construction.

A further additional object of the present invention of the present invention is to provide an integrally molded plastic shipping tray that has sufficient structural integrity to withstand repeated and rough handling.

Another object of the present invention is to provide a lightweight shipping tray with a reinforced central support member formed from a moldable material.

Another object of the present invention provides an injection molded, durable shipping tray, preferably, a one-piece injection molded, durable shipping tray.

5 A still further object of the present invention is to provide a recyclable, lightweight shipping tray.

It is yet a further object of the invention to provide a novel pallet for use with a matching hand truck to facilitate the loading and unloading of beverage trucks with beverages sorted by account order.

## 10 SUMMARY OF THE INVENTION

60457650  
15 The present invention recognizes and addresses these foregoing and other objects. The durable shipping tray of the present invention provides a convenient means for handling packaged units, in particular, packages of beverage containers. The lightweight shipping tray, or mini-pallet, can support stacked packages of beverage containers at an elevation above the floor. The primary surface or deck of the mini-pallet is substantially open, generally planar and is supported at this elevation by at least two side legs positioned proximate with the sides of the deck and a leg positioned about the center of the deck. The legs are arranged so that a portion of a carrier, such as a hand-truck, can readily be positioned sufficiently with a portion of the carrier underneath the deck to provide stable support during lifting and transporting operations. The center leg is shaped and sized to  
20 compatibly fit within a designated opening in the lifting portion of the carrier.

In the preferred embodiment, the center leg presents a continuous surface such that the carrier can be laterally moved unhindered about the leg while being positioned. Furthermore, the center legs is configured to interact with the carrier to guide and maintain the mini-pallet in a proper position

on the carrier. Also in the preferred embodiment, the deck has a lattice-like configuration with a pattern of open spaces which not only allows liquids to drain through, but also requires less material and is lighter than a solid deck.

The preferred embodiment has at least two side legs configured in the shape of rails extending a substantial width of the deck to not only provide a broad support area for the deck, but also a large surface area along the underside of the legs to enhance the wearability of the legs. A further feature of the preferred embodiment is nesting pockets for receiving the legs of an identical tray stacked thereon such that mini-pallets can be nested together.

Additional objects and advantages of the invention will be set forth in part in the following description or accompanying drawings, or may be learned through the practice of the invention.

The accompanying drawings which are incorporated in and constitute a part of the specification, illustrate several embodiments of the invention and together with the description serve to explain the principles of the invention.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

Figure 1A is a perspective view of a mini-pallet in accordance with the present invention depicted with a hand truck;

Figure 1B is a top perspective view of a mini-pallet of Figure 1A with packages positioned thereon shown in phantom;

Figure 1C is a bottom perspective view of the mini-pallet of Figure 1A;

Figure 2A is a top plan view of the mini-pallet of Figure 1A;

Figure 2B is a bottom plan view of the mini-pallet of Figure 1A, with tongue of a hand truck shown in phantom;

Figure 3 is a front elevational view of the mini-pallet of Figure 1A;



Figure 4 is a side elevational view of the mini-pallet of Figure 1A;

Figure 5 is a sectional view taken along line 5-5 of Figure 2A;

Figure 6 is a sectional view taken along line 6-6 of Figure 2A;

Figure 7 is a partial sectional view taken along line 7-7 of Figure 2B;

Figure 8 is a front elevational view showing a plurality of mini-pallets in a stacked, nested disposition.

### **DETAILED DESCRIPTION OF THE DRAWINGS**

Reference will now be made in detail to the presently preferred embodiments of the invention, one or more examples of which are illustrated in the accompanying drawings. Each example is provided by way of explanation of the invention, not limitation of the invention. In fact, it will be apparent to those skilled in the art that modifications and variations can be made in the present invention without departing from the scope or spirit thereof. It is intended that the present invention covers such modifications and variations as come within the scope of the appended claims and their equivalents.

The present invention is concerned with an improved shipping tray or “mini-pallet.” This invention can be adapted to hold numerous types of items and is especially adaptable for depicted packaged units, for instance, packaged units of beverage containers. A preferred embodiment of the mini-pallet 100 in accordance with the present invention, is in Figures 1 through 8. The mini-pallet 100 is capable of supporting individual stacks or column stacks, of various units of packaged beverage containers. The deck 102 of lightweight mini-pallet 100 can support stacked packaged units of beverage containers at an elevation above the floor.

Although the mini-pallet 100 may be formed from several connected parts, the mini-pallet 100 is preferably an integrally-molded, unitary article. The mini-pallet 100 may be injection

molded in one-piece from moldable materials such as plastics. Moldable materials may include recyclable materials such as thermoplastics and may include at least in part recycled materials. Preferably, the mini-pallet 100 is formed entirely from polyolefin polymers including polyethylene and/or polypropylene free of fillers or other reinforcing materials.

Accordingly, Figures 1B and 2A show the mini-pallet 100 comprising a deck 102 which, in a preferred embodiment, is a rectangular upper open work planar surface. In the presently preferred embodiment, the dimensions of the deck 102 are approximately 11" x 17" in size. This size has been determined adequate to accommodate a case of twelve ounce beverages and other equivalent SKU package sizes. The perimeter of the deck 102 may include a double-wall edge 128 shown in detail in Figures 5 and 6, that not only strengthens the deck 102, with respect to loads normal to the deck surface, but also provides a durable edge against impacts which may occur during handling. The double-wall edge 128 extending along the front and back 104, 105 of the deck 102 are upwardly opening, and U-shaped. These U-shaped edges have a rounded on beveled lower exterior 108. On the sides 110a, 110b of the deck 102, the double-wall edge 128 has a downwardly opening U-shaped transverse cross-sectional shape 112 to prevent trapping materials within this double-wall edge 128, as shown in Figure 5.

In Figures 1B and 2B spaced along the double-wall edge 128 are a series of stiffening ribs 150 extending between the inner and outer walls of the double-wall edge 128. In addition, there are a series of drain holes 152 extending through the double-wall edge 128 in a direction perpendicular to the deck 102 to allow any liquids that may accumulate on the surface or within the edge to drain. These stiffening ribs 150 and drain holes 152 are longitudinally spaced along the double-wall edge 128 in an alternating fashion.

As best shown in Figures 1B and 1C, the balance of the deck 102, in a preferred embodiment,

is composed of a system **154** of interconnecting, spaced-apart support members **156** which form a grid-like pattern, within the plane of the deck **102**, connecting the central support **120**, which is preferably a cylindrical leg, and rails **114a**, **114b** with the double-wall edge **128**. The support members **156** have a T-shaped transverse cross-sectional shape, as shown in Figure 5. For the maximum strength/weight performance, the support members **156** will be comprised of a horizontal portion **157a** above a vertical portion **157b** as illustrated in Figure 6. The horizontal portion **157a** forms the deck **102** while the vertical portion **157b** provides strength and rigidity to support the deck. The upper surface of the deck **102** is composed of two series of intersecting spaced-apart parallel support members **156** extending diagonally within the double-wall edge **128** that intersect at an angle dictated by the overall dimension of the deck **102**. In a preferred embodiment, the deck comprises an additional support members **158a**, **158b** extending radially outward from the central support **120** intersecting with interposing diagonally arranged support members **156** and terminating perpendicularly along the center of the front and back double-walled edge **104**, **105**, respectively. The deck **102** preferably contains many openings not only to reduce the amount of material used in manufacture, but also to permit easy drainage for any inadvertent beverage leakage.

Proximate with the sides **110a**, **110b** of the deck **102**, there are a pair of downwardly projecting rails **114a**, **114b** which act as support rails or legs. The downwardly projecting rails **114a**, **114b** extend a substantial width of the deck **102** in a direction parallel with the lateral sides. Preferably, each rail **114a**, **114b** has a corresponding rail pocket **116a**, **116b** opening upwardly through the upper surface of the deck.

Positioned about the center of the deck **102**, projecting in the same direction and approximately the same distance below the bottom surface of the deck **102** as the rails **114a**, **114b**, is a central support **120**. In the preferred embodiment, the central support **120** is cylindrical having

an outside diameter compatible with a cutout portion 21 of a tongue 20 in a compatible hand-truck 10 used as a carrier for the mini-pallet 100, as shown in Figures 1A and 2B. The preferred shape of the central support 120 is that of a cylinder, but it should be obvious to one skilled in the art that the central support 120 could be rectangular, polygonal arcuate other than circular or any other shape desired. In fact, the outer edge of the central support 120 need not have a continuous outer perimeter at all but could be comprised of multiple elements.

The circular shape allows for easy positioning of the tongue 20 of the carrier 10 about the central support 120. A multi-sided polygon could easily provide the same function, however, angular supports appear to wear more rapidly. In an alternatively preferred embodiment, an even-numbered polygon shaped central support 120 provides a similar aspect towards the front as well as to the back of the mini-pallet 100. This allows a single carrier to be utilized to pick up a loaded mini-pallet 100 from the front or from the back. The diameter of the central support 120 in the preferred embodiment is approximately 3 inches. The lower surface of the rails 114a, 114b and the central support 120 form a plane upon which the mini-pallet 100 contacts the supporting surface (such as the floor or a base of a mobile container). In the preferred embodiment, when the plane of the lower surface of the rails 114a, 114b and the central support 120 is in contact with a supporting surface, approximately 3/4" clearance is provided for the deck 102 to be supported above the supporting surface. This provides adequate clearance for the tongue 20 of a hand truck 10.

The outside diameter of the central support 120 will be determined with respect to the opening 21 in the lifting tongue 20 on the carrier designed for use with the mini-pallet 100, as shown in Figure 2B. Suitable carriers for this purpose may include customized hand-trucks, designed so that when the tray 100 is in the carrying position on the hand-truck 10 the tongue 20 extends sufficiently under the mini-pallet 100 to provide adequate support. A suitable hand-truck is the

narrow aisle configuration of hand-truck model number B16-D-1040-C45-62 available from MagLine, Inc.. Preferably, the tongue **20** interacts with the mini-pallet **100** such that when they are properly positioned the tongue **20** of the hand-truck **10** extends beyond the centerline of the mini-pallet **100**. Typically, the central support **120** will be slightly smaller than the opening **21** in the tongue **20** so the tongue **20** and central support **120** can interact to guide and maintain the mini-pallet **100** centered on the carrier. The mating aspect of the tongue **20** and central support **120** is also intended to discourage pilferage as the center segment **72** of mini pallets **120** will not permit a non-compatible handcart tongue to reach under to even the midpoint of the pallet **100**. This will make use of the pallets **100** with non-compatible hand trucks difficult.

As shown in a preferred embodiment in Figure 5, there is an upwardly opening cylindrical pocket **122** in the upper surface of the deck **102** positioned about the center of the deck **102**. The upwardly opening cylindrical pocket **122** has a base **124** parallel with the deck **102** and a generally cylindrical side wall **126** extending perpendicularly from the top surface of the deck **102** to the base **124**. The base **124** of the cylindrical pocket **122** is a substantially continuous web comprising a series of drain holes **136**. It should be apparent to one skilled in the art that cylindrical pocket **122** need not be circular in shape, but may take any shape. In a preferred embodiment, when nesting mini-pallets, the cylindrical pocket **122** receives a portion of a central support **120** of the next upward mini-pallet **100** as illustrated in Figure 8.

Coaxial with the cylindrical pocket **122** and extending from the underside of the base **124** is a central support **120**. The central support **120** projects in the same direction and to substantially the same distance below the bottom surface of the deck **102** as the rails **114a**, **114b**. The support base **118a**, **118b** of the rails **114a**, **114b** and the distal end **144** of the central support **120** as shown in Figure 3 define a plane upon which the mini-pallet **100** contacts the floor or other supporting

surface.

As shown in Figures 4 and 5, the ends of the rails **114a**, **114b** extend upwardly and outwardly to form an end bevel **134** which assists in guiding the rails **114a**, **114b** into a corresponding rail pockets **116a**, **116b** of an identically shaped mini-pallet **100**, upon which it is to be nested, during stacking nested pallets as shown in Figure 8. The degree of bevel in the preferred embodiment is approximately 45 degrees. As shown in Figure 4, the rail end bevel **134** angles inward from the front and back edges of the deck **102**. This not only minimizes the chances of strikes from the carrier but also reduces the force from such a strike by deflecting the impact downwardly. Preferably, the angle of the bevel **134** is such that it not only assists in positioning a leg, or rail **114a**, **114b** within a corresponding mini-pallet **100**, during stacking, but also minimizes the lateral movement of the mini-pallets **100** once in a nested position.

As shown in Figure 7, the support base **118a** of the rail **114a** is substantially formed from a series of spaced apart bridging ribs **130** extending between the opposing sides of the given rail **114a**, **114b**. These bridging ribs **130** have an essentially inverted T-shaped transverse cross-sectional shape, comprising a horizontal base **131a** and a vertical support member **131b**. These inverted T-shaped bridging ribs **130** provide a substantial areas of material from their horizontal sections **131a** to form the support base **118a**, and added strength through the vertical sections **131b**. This offers a support base with superior rigidity. Positioned along the support base between the bridging ribs **120** is at least one drain hole **132** which communicates between the rail pocket **116a** and the outer surface of the rail **114a**.

The top surfaces of the vertical sections **131b** of the bridging ribs **130** may be coplanar with the upper surface of the base **124** of the cylindrical pocket **120** and together form a stop means. When two or more mini-pallets **100** are nested the support bases **118a**, **118b** of an upper mini-pallet



100 rest upon the upper surface of the bridging ribs 130, as shown in Figure 8. Similarly, the distal end 144 of the cylindrical leg 120 will rest upon the base 124 of the lower mini-pallet 100.

As shown in Figure 8, the rails 114a, 114b, rail pockets 116a, 116b, central support 120 and cylindrical pocket 122 combine, in the preferred embodiment, to provide the nesting capability of the mini-pallet 100. The term “nesting” refers to the ability of one mini-pallet 100 to be positioned on top of another so that the vertical components of the two mini-pallets 100 are such that the overall height is less than the sum of the height of the individual mini-pallets 100. For instance, the rails 114a, 114b and rail pockets 116a, 116b may be tapered, as shown in Figures 3 and 5, so that the upper end of a rail pocket 116a or 116b defines an area larger than, and therefore capable of, receiving the lower portion of the rail 114a, 114b. Similarly, the inside diameter of the cylindrical pocket 122 should be sufficiently large enough to accommodate the outside diameter of the central support 120, as shown in Figure 5.

In order to provide a secure fit when nesting multiple mini-pallets 100, a preferred embodiment shown in Figure 2A utilizes fitting beads 170 and fitting teeth 172 located either within, or in close proximity to the rail pockets 116a, 116b. The fitting beads and/or fitting teeth of a first mini-pallet 100 will contact a rail 114a, 114b when a second mini-pallet 100 is nested atop the first mini-pallet 100. The fitting beads 170 may restrict side-to-side movement of a nested mini-pallet 100. The fitting teeth 172, may restrict front to back movement of a nested mini-pallet 100. One skilled in the art will know that restricting movement in one direction will likely result in restriction in movement in a perpendicular direction as well. Therefore fitting beads 170 will likely restrict movement of a nested mini-pallet from front-to-back as well as from side-to-side. It should be evident to one skilled in the art that the fitting teeth 172 and fitting beads 170 need not be utilized together in a single rail pocket 116a, 116b. It should also be obvious to one skilled in the art that

the fitting beads 170 and fitting teeth 172 may be utilized singularly rather than in multiples as depicted in the drawings. Fitting beads 170 and fitting teeth 172 are fabricated as an integral part of the mini-pallet 100 in a presently preferred embodiment, however, one skilled in the art will know that other materials such as rubbers, other plastics, etc., may be utilized. Fitting teeth 172 may also engage with notches 174 and the end levels 134 of rails 114a, 114b as shown in Figure 3.

In a presently preferred embodiment, concentrically positioned inside the central support 120 is a cylindrical support 140. Extending radially from the cylindrical support 140 outwardly to the central support is a series of spaced apart reinforcing ribs 142, as shown in Figure 2B. The combination of the radially extending ribs 142 and cylindrical support 140 combine to provide a lateral support structure for the central support 120 which improves its ability to withstand forces imposed transverse to its axis. For instance, the force imparted by the tongue of a carrier during transport of the mini-pallet 100 with stacked beverage containers or empty mini-pallets 100 positioned thereon. Typically, the central support 120 and radially extending ribs 142 will extend from the plane defined by the distal end 144 of the cylindrical leg 120 up to the base 124 of the cylindrical pocket. Additionally, in a preferred embodiment, aside from the radially extending reinforcing ribs 142 and the cylindrical support 140, the interior of the central support 120 is downwardly open from the underside of the cylindrical base so as to prevent trapping of debris within the leg.



We claim:

1. A mini-pallet comprising:

a substantially rectangular deck having an upper surface and having a perimeter comprising at least one double wall edge;

two downwardly projecting rails connected to said deck,

a downwardly projecting central support connected to said deck, and located intermediate of said two downwardly projecting rails.

2. The mini-pallet of claim 1 wherein said deck, said downwardly projecting rails and said central support are integrally connected.

3. The mini-pallet of claim 1 wherein said deck has two lateral sides which are approximately parallel and said downwardly projecting rails extend substantially a width of the deck in a direction parallel with said two lateral sides.

4. The mini-pallet of claim 3 wherein said vertical support is less than half the width of the deck in a direction parallel with said two lateral sides.

5. The mini-pallet of claim 1 wherein said at least one double-wall edge further comprises at least two stiffening ridges longitudinally spaced along and connected to said at least one double-wall edge.

6. The mini-pallet of claim 5 wherein said double-wall edge has a U-shaped transverse cross-section, and further comprises at least two drain holes located on said at least one double-wall edge.

7. The mini-pallet of claim 1 wherein said deck further comprises a plurality of spaced-apart linear support members and at least two openings providing communication from the upper surface through the deck.

8. The mini-pallet of claim 7 wherein said linear support surfaces have a horizontal deck forming portion and a vertical reinforcing portion.
9. The mini-pallet of claim 7 wherein said linear support members have a T-shaped cross-sectional shape.
- 5 10. The mini-pallet of claim 7 wherein said deck further comprises a plurality of radially extending reinforcing ribs.
11. The mini-pallet of claim 7 wherein said spaced-apart linear support members form a grid-like pattern among said openings connecting said central support, said downwardly projecting rails, and said double-wall edge.
- 10 12. The mini-pallet of claim 1 further comprising a rail pocket opening upwardly through the upper surface of said deck, compatible with a downwardly projecting rail of a similarly shaped mini-pallet, and adapted to receive at least a portion of said similarly shaped mini-pallet rail when multiple mini-pallets are nested.
- 15 13. The mini-pallet of claim 12 further comprising a fitting bead within the rail pocket configured to contact a similarly configured mini-pallet's downwardly projecting rail when the similarly configured mini-pallet is nested atop the mini-pallet.
- 16 14. The mini-pallet of claim 12 further comprising a fitting tooth within the rail pocket configured to contact a similarly configured mini-pallet's downwardly projecting rail when the similarly configured mini-pallet is nested atop the mini-pallet
- 20 15. The mini-pallet of claim 1 wherein said downwardly projecting rails further comprise at least two lateral walls with bridging ribs, a horizontal base to form a lower surface of said projecting rails, and a vertical support member.
16. The mini-pallet of claim 15 wherein said bridging ribs have an inverted T-shaped cross-

section.

17. The mini-pallet of claim 1 wherein said central support has a substantially continuous circular outer perimeter.

18. The mini-pallet of claim 1 wherein said central support has a substantially continuous arcuate outer perimeter.

19. The mini-pallet of claim 1 wherein said central support has an outer edge defining an even-sided polygon.

20. The mini-pallet of claim 1 wherein said central support is compatible with a recessed portion in a tongue of a carrier.

21. The mini-pallet of claim 1 further comprising a pocket on the upper surface of the deck coaxial with said central support and adapted to receive at least a portion of a similarly shaped mini-pallet's central support when multiple mini-pallets are nested.

22. The mini-pallet of claim 2 wherein said pocket further comprises reinforcing ribs connected to an interior surface of said pocket.

23. A shipping tray comprising:

a deck having a pair of opposing lateral sides, said opposing lateral sides being substantially parallel;

a plurality of downwardly extending legs proximate with said opposing lateral sides;

a central support extending downwardly from about the center of said deck;

said deck above at least a portion of said plurality of legs and said central support;

said central support having an exterior surface, and a pocket capable of receiving at least a portion of a similarly configured second shipping tray's central support when said second shipping tray is nested atop the shipping tray.

24. A tray comprising:

a deck;

two legs extending from a bottom surface of said deck;

two rail pockets located on a top surface of said deck and compatible to receive at least a portion of a similarly shaped tray's legs when said trays are stored in a nested position;

a central support located near the center of said deck, extending from a bottom surface of said deck, and having an outer perimeter portion compatible with a portion of a tongue of a carrier; and

a cylindrical pocket located on a top surface of said deck compatible to receive at least a portion of a similarly shaped tray's central support when said trays are in a nested position.

25. A method for distributing beverages from a truck utilizing at least one mini-pallet of the type having a deck having two downwardly projecting rails, a downwardly projecting central support intermediate the two downwardly projecting rails, and a pocket coaxial with said central support adapted to receive at least a portion of a similarly shaped mini-pallet's central support when multiple mini-pallets are nested, said method consisting of the following steps:

- a. loading the mini-pallet with at least a part of a customer order to form a beverage stack;
- b. placing the pallet on a truck
- c. driving the truck having at least one beverage stack to a desired location;
- d. placing a tongue of a hand-truck under the mini-pallet, said tongue having a compatible recess adapted to coordinate with the central support of said mini-pallet;


- e. lifting said mini-pallet with the hand-truck into a loaded position;
- f. maneuvering said loaded hand-truck towards an open door of said truck;
- g. off-loading said loaded hand-truck from said truck; and
- h. maneuvering said hand-truck to an intended location.
- i. unloading said beverage stack from said hand truck.

5

RECEIVED

## ABSTRACT

The present invention provides a novel mini-pallet to create and organize product stacks. In a preferred configuration, the mini-pallet is a nestable lightweight shipping tray which provides a convenient means for handling packaged units, in particular packages of beverage containers. The mini-pallet can support loads at an elevation above a supporting surface through the use of a deck supported by two side legs and a central support. The legs are located to facilitate a user in positioning a carrier under the deck for transportation. The central support, in a preferred embodiment, compatibly fits with a designated opening in the lifting portion of the carrier. When not loaded, the mini-pallet is capable of “nesting” within another mini-pallet for convenient storage.






Fig. 1B

(18)

[illegible]



650230" 6045760




Fig. 1C  
(formerly 4A)




FIG. 2A 6-

FIG. 5 144

୧୫୫

650250 "E049T E60

P. 11




FIG. 2B

3394840

JUN-10-1998 10:39

P. 11

FIG. NO. 3394840

JUN-10-98 WED 10:45 AM KHHK16

650290-049760




Fig. 6  
(family 4C)




Fig. 3  
(family 4D)

650250-2045760




FIG. 4




FIG. 7





FIG. 8





RULE 63 (37 C.F.R. 1.63)  
DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATION  
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name, and I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

IMPROVED SHIPPING TRAY

the specification of which (check applicable box(s):

[X] is attached hereto.

[ ] was filed on \_\_\_\_\_ as U.S. Application Serial No. \_\_\_\_\_.

[ ] was filed as PCT International application No. PCT// on \_\_\_\_\_  
and (if applicable to U.S. or PCT application) was amended on \_\_\_\_\_.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to the examination of this application in accordance with 37 C.F.R. 1.56(a). I hereby claim foreign priority benefits under 35 U.S.C. 119/365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed or, if no priority is claimed, before the filing date of this application:

Prior Foreign Application(s):

Application Number

Country

Day/Month/Year Filed

I hereby claim the benefit under 35 U.S.C. 120/365 of all prior United States and PCT international applications listed above or below and, insofar as the subject matter of each of the claims of this application is not disclosed in such prior applications in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose material information as defined in 37 C.F.R. 1.56(a) which occurred between the filing of the prior application and the national or PCT international filing date of this application:

Prior U.S./PCT Application(s):

Application Serial No.

Day/Month/Year Filed

Status; patented,  
pending, abandoned

| Application Serial No. | Day/Month/Year Filed | Status  |
|------------------------|----------------------|---------|
| 60/094,439             | 28/07/98             | pending |
| 29/088,283             | 20/05/98             | pending |
| 60/086,135             | 20/05/98             | pending |

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

And I hereby appoint Alan Ruderman, Reg. No. 25,369, Douglas T. Johnson, Reg. No. 31,841, Charles W. Forlidas, Reg. No. 41,758, and Stephen J. Stark, Reg. No. 43,152, with the law firm of Miller & Martin, 1000 Volunteer Building, 832 Georgia Avenue, Chattanooga, Tennessee 37402, telephone number (423) 756-6600, my attorney to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith and with the resulting patent and to whom all communications are to be directed.

1) Inventor's Signature Phillip C. Hwang Date 5/12/99  
Inventor's Name (typed) Phillip C. Hwang USA  
First Middle Initial Family Name Citizenship  
Residence (City) Los Angeles (State/Foreign Country) CA  
Post Office Address 4010 East 26<sup>th</sup> Street Zip Code 90023

2) Inventor's Signature William P. Gms Date 5/11/99  
Inventor's Name (typed) William P. Gms USA  
First Middle Initial Family Name Citizenship  
Residence (City) Los Angeles (State/Foreign Country) CA  
Post Office Address 4010 East 26<sup>th</sup> Street Zip Code 90023

3) Inventor's Signature \_\_\_\_\_ Date \_\_\_\_\_  
Inventor's Name (typed) Norman E. Strohfus USA  
First Middle Initial Family Name Citizenship  
Residence (City) Eagan (State/Foreign Country) MN  
Post Office Address 2750 Eagandale Blvd. Zip Code 55121

FOR ADDITIONAL INVENTORS, check box [X] and attach sheet with same information and signature and date for each. 1

